

# T4 Procedure Chair

## Common Applications: Surgical, Endoscopy, GI, and Emergency

The T4 can be incorporated across a spectrum of applications and environments. With its universal appeal, it is often utilized as a procedure and/or transport chair. When seconds can save lives, you need multi-purpose medical seating solutions.



Admission



Transport



Procedure



Discharge

## Our redesigned T4 offers even more **clinical** and **economic** advantages to doctors and patients.

From the new sleek color to the new battery to the new triple column base—we've taken a successful procedure chair and made it even better.

- The new battery system eliminates the inconsistencies often found in other battery-operated medical chairs.
- Powered positioning with memory presets helps eliminate the need for patient transfers and reduce the risk of injuries to patients and staff while improving patient throughput.
- This "one patient, one surface" design contributes to a more spa-like environment, which can soften the harsh aesthetic of traditional surgery centers and create a more comfortable experience for patients.
- The space-saving feature is especially important in alternate site locations. In the seated position, the T4 requires half the space of a traditional stretcher and is easy to navigate through hallways, elevators, and other close quarters. Plus, the small footprint frees up floor space so additional units can be stored more efficiently.

### Details doctors want to know.

- A compact wheelbase and powered height range of 23.5" to 43.5" (59.69 cm - 110.49 cm) and 22" to 42" (55.88 cm - 106.68 cm on the T4-LB) provides superior surgeon/patient access during procedures.
- The T4, popularly known as the universal care platform, boasts innovative powered patient positioning that helps reduce patient transfers, limiting the risk of injury to patients and caregivers across a variety of healthcare settings.
- Trendelenburg positioning provides efficient functionality and surgical access during procedures.

### New Additions!



On-Board Charging  
Lithium-ion Battery




Memory Presets





The T4 Procedure Chair embodies our One Patient, One Surface® philosophy: Each patient remains on one surface throughout their visit—comfort, safety, efficiency, and functionality combined! One piece of equipment also means cost savings, space savings, and time savings. Invest in a procedure chair that puts patients first and affords precise positioning for surgeons, easy access for caregivers, and smoother transport for medical staff.



## Standard Features

Radiolucent back • Push-button pendant • Central locking brake • Swing & tuck side rails • Electrostatic discharge steering caster

## Specifications

	T4-XB	T4-B	T4-LB	T4-WB
<b>Wheelbase</b> (length x width)	33" x 20" 83.80 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm
<b>Weight Capacity</b>	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg
<b>Seat Height</b> (low ♦ high)	23.5" ♦ 43.5" 59.59 cm ♦ 110.49 cm	23.5" ♦ 43.5" 59.60 cm ♦ 110.50 cm	22" ♦ 42" 55.88 cm ♦ 106.68 cm	23.5" ♦ 43.5" 59.59 cm ♦ 110.49 cm
<b>Back Width</b>	24" / 60.96 cm	24" / 60.96 cm	24" / 60.96 cm	28" / 71.12 cm
<b>Side Rail Height</b> (up, seat pan to rail top) ♦ <b>Length</b>	13.5" ♦ 27.5" 34.29 cm ♦ 69.85 cm	13.5" ♦ 27.5" 34.29 cm ♦ 69.85 cm	13.5" ♦ 27.5" 34.29 cm ♦ 69.85 cm	13.5" ♦ 27.5" 34.29 cm ♦ 69.85 cm
<b>Overall Chair Height</b> (low ♦ high)	56" ♦ 76" 142.24 cm ♦ 193.04 cm	56" ♦ 76" 142.24 cm ♦ 193.04 cm	54.5" ♦ 74.5" 138.43 cm ♦ 189.23 cm	56" ♦ 76" 142.24 cm ♦ 193.04 cm
<b>Seat Width</b>	24" / 60.96 cm	24" / 60.96 cm	24" / 60.96 cm	28" / 71.12 cm
<b>Overall Width</b> (rails up)	31" 78.74 cm	31" 78.74 cm	31" 78.74 cm	35 88.90 cm
<b>Patient Surface Length</b> (standard ♦ with optional manual folding footrest)	77" ♦ 71" 195.58 cm ♦ 180.34 cm	77" ♦ 71" 195.58 cm ♦ 180.34 cm	77" ♦ 71" 195.58 cm ♦ 180.34 cm	77" ♦ 71" 195.58 cm ♦ 180.34 cm
<b>Backrest Articulation Range</b>	0° - 90°	0° - 90°	0° - 90°	0° - 90°
<b>Charging System Input Volts</b>	120-240 VAC	120-240 VAC	120-240 VAC	120-240 VAC
<b>Charging System Current</b>	350 mA	350 mA	350 mA	350 mA
<b>Charging System Frequency</b>	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
<b>Charging System Max Power</b>	38.5 W	38.5 W	38.5 W	38.5 W

## Available Accessories

Head Pillow • Lap Belt With Buckle • IV Pole • Oxygen Tank Holder • Arm Board • Side Table With Cushion • Stirrups